



JOIST & FLASHING TAPE INSTALLATION

Self-adhesive butyl tape for composite or wood decks

Joist and Flashing Tape will protect and maximize the life of your wood or composite deck's substructure. Joist and Flashing Tape can be applied to the top of joists, rim joists, stair stringers, stair treads, blocking, and ledgers to protect wood against water damage.

Available Sizes: 1-5/8 in. x 50 ft. (for single-Joist) and 3-1/8 in. x 50 ft. (for double-Joist/beam)

Joist and Flashing Tape acts as a moisture barrier slowing the wood deterioration. This will maintain the holding power of deck screws for a longer period of time.

Ideal for both wood and composite deck understructures for which we recommend using professional grade treated lumber.



Step 1

Ensure all application areas are dry, clean, and clear of debris.



Step 2

Peel back the protective film a foot at a time to make it more manageable. Then begin laying the tape to the desired area. Apply hand pressure to the tape after applying to ensure maximum adhesion.



Step 3

Once application is complete, trim any excess with scissors or a utility knife.



THE DIAGRAMS AND INSTRUCTIONS IN THIS BROCHURE ARE FOR ILLUSTRATION PURPOSES ONLY AND ARE NOT MEANT TO REPLACE A LICENSED PROFESSIONAL. ANY CONSTRUCTION OR USE OF THE PRODUCT MUST BE IN ACCORDANCE WITH ALL LOCAL ZONING AND/OR BUILDING CODES. THE CONSUMER ASSUMES ALL RISKS AND LIABILITY ASSOCIATED WITH THE CONSTRUCTION OR USE OF THIS PRODUCT. THE CONSUMER OR CONTRACTOR SHOULD TAKE ALL NECESSARY STEPS TO ENSURE THE SAFETY OF EVERYONE INVOLVED IN THE PROJECT, INCLUDING, BUT NOT LIMITED TO, WEARING THE APPROPRIATE SAFETY EQUIPMENT. EXCEPT AS CONTAINED IN THE WRITTEN LIMITED WARRANTY, THE WARRANTOR DOES NOT PROVIDE ANY OTHER WARRANTY, EITHER EXPRESS OR IMPLIED, AND SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING CONSEQUENTIAL DAMAGES.