



VOYAGE DECKING



VOYAGE COSTA AND KHAYA AND DARK SLATE PICTURE FRAME BOARD
WITH CONTEMPORARY CABLE RAILING IN TEXTURED BLACK


Voyage decking featuring Surestone® technology combines durability and style for outdoor spaces that perform in every condition. With enhanced traction and heat-resistance, Voyage delivers real-wood looks and enduring performance that stands up to whatever your outdoor life demands.



ENHANCED
TRACTION



HEAT
RESISTANCE



GROOVED-EDGE PROFILE

Width: 3-1/2", 7-1/4"
Length: 20'

Width: 5-1/2"
Length: 12', 16', 20'



SOLID-EDGE PROFILE

Width: 3-1/2", 7-1/4", 9-1/4"
Length: 20'

Width: 5-1/2"
Length: 16', 20'



5 WIDTHS
AVAILABLE



SIERRA

TUNDRA

MESA

COSTA

KHAYA

SEDONA


11 1/4" - STEP TREAD

Available in Khaya and Tundra
Length: 13'

Fascia available in 8"
and 11 1/4" in 12' lengths



Learn more here:



Virtually no thermal expansion or contraction



Nearly 35% lighter than traditional composites and similar in weight to PVC



Warranted for installation in or in contact with the ground or water

ALL DECKORATORS DECKING



Developed for the demands of modern outdoor living, Surestone® technology is engineered with proprietary, performance-driven materials designed for lasting strength and timeless beauty. From the first plank to every moment after, your deck is secure, resilient, and unmistakably refined. Every step feels solid, every surface delivers confidence, and every space makes a statement. With Deckorators, your deck isn't just built to last – it's built to stand out.



SEE HOW VOYAGE STACKS UP AGAINST THE LEADING PVC DECKING:

PROPERTY	Dec o rators® VOYAGE DECKING	LEADING PVC DECKING
Weatherability	✓	✓
Scratch-resistant	✓	✓
Stain-resistant	✓	✓
All ingredients unaffected by moisture, sun or microbes	✓	
Best stiffness-to-weight ratio of any thermoplastic deck board in the industry	✓	
Strength:weight ratio (MOR at ambient temp with no environmental or safety factors applied)	2608.7 (4200 psi, 1.61 lbs/lf)	2292.99 (3600 psi, 1.57 lbs/lf)
Cannot be broken in flexural loading or impact	✓	
Maximum deflection at midspan (Uniform load - 100 /sq. ft. at 16" o.c.)	0.03323062 (.835" x 5.5")	0.04067322 (1" x 5.5")
Lowest thermal expansion/contraction of any thermoplastic deck board in the industry	✓	
Thermal movement (50°F temp swing on a 12 ft deck board)	0.06768	0.17112
25-year removal and replacement warranty, including water and ground contact	✓	
Enhanced traction	✓	
Heat resistance	✓	

Order **FREE** samples today:



DECKORATORS.COM/VOYAGE



THE COLORS REPRESENTED HEREIN ARE REPRODUCED WITH PRINTER'S INKS AND MAY VARY FROM ACTUAL FACTORY PRODUCTS. FOR ACTUAL PRODUCT COLORS AND FINISHES, PLEASE VISIT YOUR DECKORATORS DEALER.

©2025 Deckorators, Inc. All rights reserved. Deckorators is a registered trademark of Deckorators, Inc. 15824_10/25



Official Decking
and Railing